


A DECORATIVE CONCRETE TREATMENT

PACKAGING



MIXING



APPLICATION



USES



SUBSTRATES

CONCRETE FLOORS
DRIVEWAYS
PATHS

DESCRIPTION

A chlorinated rubber based stain for concrete and brick substrates. Driveway Stain corrects natural imperfections and stains with uniform colour without disturbing the natural texture of the substrate.

USES

A stain for concrete, driveways, paths, patios etc.

FEATURES

Corrects staining and colour imperfections. Is abrasion and chemical resistant. Will not blister or peel.

DRYING TIME

1 1/2 hours at 25°C.

COVERAGE (Approximate)

Wood float – 5-7m²/litre/coat (two coats are required). 3 coats may be required on some substrates.

COLOURS

Available in six colours.

PERFORMANCE DATA

Adhesion to Substrate (ASTM D4541) 3Mpa

Water permeability (BS1881. part 5 test 6)

24 hour 0.001 lml/m²/sec

i.e. Reduces water absorption by 98%

Chemical Resistance

Resistant to mild acids and alkali attack. Not resistant to petroleum solvents.

Slip resistance AS366.1

Acid etched, coated wet surface 0.6 l

SPECIFICATIONS

The concrete treatment shall be a solvent based chlorinated rubber sealer which will impregnate into the surface of the concrete have a minimum adhesion to substrate of 3Mpa and reduce water absorption by 98% such as Driveway Stain manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers instructions.

SURFACE PREPARATION

Acid etch the surface to be coated to obtain good penetration. Apply only to sound, dry, clean surfaces. Remove grease, oil, paint and contaminants. Do not apply to powdery or weak surfaces or clay pavers.

New concrete must be allowed to cure for 28 days.

Acid etch with Hydrochloric acid diluted with 2 parts water, applied with a plastic watering can and a stiff broom (1 litre per m²). Leave for 10-15 minutes and thoroughly wash residue away with large quantities of clean water whilst brushing with a stiff broom – allow to dry.

Remove surface dust, oil, grease and other contaminants by washing the surface with a detergent then wash thoroughly with clean water and allow to dry.

APPLICATION

Apply the first coat diluted 20% with solvent; then apply a second coat allowing approximately 1 1/2 hours at 25°C between coats. Apply the first coat at a rate of 5m²/litre and the second at 7m²/litre.

Apply Driveway Stain with a low pressure spray, roller or soft brush and allow the coating to dry thoroughly before putting into use. Apply Driveway Stain using a uniform application direction and method to obtain uniformity of colour, thickness and appearance.

When applying over **Concrete Hardener** (to case harden the concrete) apply the Driveway Stain after 24 hours.

PRECAUTIONS

- In its wet state Driveway Stain is highly flammable.
- Adequate ventilation must be provided when applying in confined spaces.
- Undue contact with the skin should be avoided.
- Do not apply to clay pavers.
- Do not use in areas subject to solvent spillage.

STORAGE

Keep in a cool dry place away from open fires, heater and stoves etc.

SAFETY INSTRUCTIONS

Contains flammable solvents in the liquid state. Do not smoke during application or apply in the presence of naked flames, electrical equipment or sparks. Ensure adequate ventilation during application and drying period. Avoid contact with skin or eyes, breathing vapour or mist spray. Keep out of children's reach.

SOLVENT

Xylene or similar.

FIRST AID

If swallowed do not induce vomiting. Give a glass of water and contact a doctor or Poisons Information Centre.

FURTHER INFORMATION

Further information on this product is contained in the Material Safety Data Sheet.

SHELF LIFE

2 years



● **ADELAIDE** 467 - 469 SOUTH RD REGENCY PARK 5010 PH: (08) 8346 8013 FAX: (08) 8340 2052
● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
● **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
● **SYDNEY** 2/ 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
40000 SHAB ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526