

**PACKAGING**



**MIXING**



**APPLICATION**



**USES**



**FLOOR**



**WALL**

**SUBSTRATES**

CONCRETE  
BRICK  
BLOCK  
RENDER WALLS

**DESCRIPTION**

Quickcrete is a mortar designed for jobs requiring a fast set and high strength. Quickcrete is ready to use, just add water, no other additives required.

**USES**

- Sealing plumbing pipes
- Setting toilet pans
- Grouting and patching

**COVERAGE** (approximate)

200 x 10kg bags = m<sup>3</sup>

**PERFORMANCE DATA**

Compression Strength 29Mpa (unconstrained)

**SPECIFICATION**

The fast setting mortar shall be Quickcrete manufactured by Construction Chemicals and shall be applied in accordance with the manufacturer's application instructions.

**MIXING**

Place water in a suitable mixing container and slowly add powder stirring continually to achieve a stiff paste. Do not mix more than can be used within 10 minutes. Do not use any additives.

**POT LIFE**

20 mins at 25°C @ 50% R.H.

**APPLICATION**

Apply mortar with a trowel or similar tool. Do not overwork as this will decrease the product's overall strength. Set time is 15 minutes @ 20°C but will vary according to temperature. Sealing leaks in masonry walls can be done by waiting 5-10 mins after mixing then plugging the hole and holding in position until set.

**FIRST AID**

Contains cement which may cause irritation. Wear gloves on mixing and application. If swallowed, do not induce vomiting. Give a glass of water and seek medical advice.

**CLEANUP**

Clean up in water.