

## WHITE PREMIXED NON-SLIP FLEXIBLE WALL ADHESIVE

### PACKAGING



### MIXING




### APPLICATION



WALLS-6mm Notch

### USES



### SUBSTRATES

GYPSUM BUILDING  
BOARD  
CEMENT SHEET  
CEMENT RENDER  
BRICK, BLOCK  
CONCRETE

### DESCRIPTION

TILEMASTIC is a premium, white premixed, water resistant, flexible wall tile adhesive with excellent non-slip properties and bond strength.

### USES

Fixing all types of ceramic wall tiles to clean and firm walls of plaster, gyprock, cement sheeting and cement render in kitchens, bathrooms and laundries. TILEMASTIC is especially designed for large tiles (300mm sq./1.5 kg) and tiling from the top (eliminating the need for straight edges).

**Do not use between two non porous surfaces as the adhesive will not set. Not suitable for immersed applications, Construction Chemicals provide other systems.**

### PERFORMANCE DATA

Exceeds the performance requirements of AS4992.

### SPECIFICATION

The ceramic tile adhesive shall be a premixed flexible acrylic adhesive that exceeds the requirements of AS4992 and has a minimum shear bond strength of 3.44 MPA such as TILEMASTIC manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

### SURFACE PREPARATION

Surfaces must be structurally sound, free from dirt, dust, grease and other contaminants. Cement render must be 7 days old. Building boards must be firmly fixed at 450mm centres to restrain movement with rough side out where possible. Remove any paint and prime highly absorbent surfaces (ie. cement sheeting) with PRIMER & GROUT ADDITIVE and allow to dry before application of adhesive.

### APPLICATION

Apply the TILEMASTIC with a 6mm x 6mm notched trowel. Spread only 1m<sup>2</sup> at a time as the adhesive dries rapidly. Immediately press dry tiles into the ribs of the adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Remove any excess adhesive from the surface of the tile before it dries using a damp cloth. The adhesive bed should be not less than 1.6mm or greater than 3.0mm thick.

### COVERAGE

2Kg per m<sup>2</sup> (approximately)

### GROUTING

Allow 24 hours before commencing, longer in cold damp conditions or when using dense tiles. Use PRIMER & GROUT ADDITIVE with KEMGROUT.

**CONSTRUCTION  
CHEMICALS**

- **ADELAIDE** 135 CORMACK RD (Cnr Davis St) WINGFIELD 5013 PH: (08) 8243 7888 FAX: (08) 8243 7800
- **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
- **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
- **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
- **SYDNEY** 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
- **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
- **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING 40000 SHAB ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

[www.constructionchemicals.com.au](http://www.constructionchemicals.com.au)

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."