

PREMIXED NON-SLIP FLEXIBLE ACRYLIC ADHESIVE

PACKAGING



MIXING




APPLICATION



USES

USES



SUBSTRATES

GYPSUM BUILDING
BOARD
CEMENT SHEET
CEMENT RENDER
BRICK, BLOCK
CONCRETE

DESCRIPTION

TRADEMASTIC is a white premixed thin bed acrylic based ceramic tile adhesive with non-slip properties.

USES

Fixing ceramic and mosaic tiles to clean and firm walls of plaster, gypsum building board, cement sheeting, cement render in kitchens, bathrooms and laundries.

FEATURES

- Non-slip
- Flexible
- Easy application

COVERAGE (Approximate)

1 m²/litre (1.5kg)

PERFORMANCE DATA

Exceeds the performance requirements of AS4992

Shear Bond Strength (2.85Mpa)

SPECIFICATION

The ceramic tile adhesive shall be a premixed flexible acrylic adhesive that exceeds the requirements of AS4992 and has a minimum shear bond strength of 2.85Mpa such as TRADEMASTIC manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers application instruction.

SURFACE PREPARATION

Surfaces must be free from dirt, dust, grease, and other contaminants. Building boards must be firmly fixed at 450 mm centres to restrain movement with rough side out where possible. Remove paint and prime highly absorbent surfaces (i.e. cement sheeting) with PRIMEBOND and allow to dry before application of adhesive.

APPLICATION

Apply the TRADEMASTIC with a notched trowel. Spread only 1 m² at a time as the adhesive dries rapidly.

Immediately press dry tiles into the ribs of adhesive ensuring that all of the tile is in contact with the adhesive before it dries. Remove any excess adhesive from the surface of the tile before it dries using a damp cloth. The adhesive bed should not be less than 1.6mm or greater than 3.5mm thick.

CAUTION

Do not use the adhesive between two impervious surfaces as the adhesive will not set.

Do not use in permanently immersed / ponded situations.

Do not use over waterproof membranes.

GROUTING

Allow 24 hours before commencing, longer in cold damp conditions or when using dense tiles. Then use KEMGROUT FLEXIBLE.

SHELF LIFE 2 years

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 135 CORMACK RD (Cnr Davis St) WINGFIELD 5013 PH: (08) 8243 7888 FAX: (08) 8243 7800
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
 ● **SYDNEY** 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

www.constructionchemicals.com.au

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."