

Vertical Fixing of Tiles/Stone

PACKAGING




MIXING



APPLICATION



USES



ADHESIVE FIX



PIN OR BRACKET FIX

SUBSTRATES

EXTERNAL
CONCRETE
CEMENT RENDER
BRICK, BLOCK
INTERNAL
BUILDING BOARDS
CEMENT / GYPSUM

	Adhesive Fix	Pin or Bracket Fix
Tile/Stone Weight	Under 4kg per tile	Over 4kg per tile
Fixing height	Under 3m	Over 3m
Load bearing capacity of substrate	must not be exceeded	

GUIDE TO SUBSTRATE LOAD BEARING CAPACITY:

Concrete	60kg/m ²
Cement Render	32kg/m ²
Masonry, Brick, Block	32kg/m ²
Building Boards (cement/gypsum)(internal only)	
Fixed at 100mm centre	32kg/m ²
Fixed at 200mm centre	15kg/m ²

PRIMER:

PRIMAX

ADHESIVE:

ELASTACRETE and KEMGRIP (floor and wall)

PRECAUTIONS:

External tiling:

Use the wet weight of the tile or stone.

Always consider the load bearing of the tile/stone/substrate when wet.

BUILDING BOARDS ARE FOR INTERNAL FIXING ONLY.

The weight of render 20kg/m² at 12mm thick must be considered when bonding to a rendered substrate.

The technical sheet is written as a guide only. Consider Occupational Health & Safety Issues and good trade practice. An engineer must be consulted to consider site, environmental factors and weight loading outside these guide lines.

All applications to A.S. 3958.1 2007. Tiles over 400x400 require a 12mm notch trowel and tile back buttered.

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 135 CORMACK RD (Cnr Davis St) WINGFIELD 5013 PH: (08) 8243 7888 FAX: (08) 8243 7800
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
 ● **SYDNEY** 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 40000 SHAH ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

www.constructionchemicals.com.au

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."