

**CERAMIC TILE
ADHESIVES
& GROUTS**

Dribond

**WATERPROOFING PRODUCTS
FOR CONCRETE AND MASONRY**

WEB SITE

www.constructionchemicals.com.au

Adelaide
135 Cormack Rd
Wingfield S.A. 5013
Ph: (08) 82437888
Fax: (08) 82437800
Email
admin@constructionchemicals.com.au

ABN 66 008 091 503

Brisbane
45 Coulson Street
Wacol Qld 4076
Ph (07) 32712944
Fax (07) 32713892
Email
conchem.qld@bigpond.com.au

Melbourne
11 Gabrielle Court
Bayswater North Vic 3153
Ph (03) 97614711
Fax (03) 97614748

Perth
11 Collie Road
Welshpool W.A. 6106
Ph (08) 93569999
Fax (08) 93569955

Sydney
2 / 31-33 Newton Road
Wetherill Park N.S.W. 2164
Ph (02) 97563533
Fax (02) 97563534

Auckland
16 Carpenter Road
East Tamaki N.Z.
Ph (09) 2735444
Fax 0800266236

Kuala Lumpur
Lot 2 Jalan Kecepi,
33/2 Elite Industrial Estate
Off Jalan Bukit Kemuning
40000 Shah Alam
Ph (603) 51222522
Fax (603) 51222526

MATERIAL SAFETY DATA SHEET

Issued 08/10/2002

Revised 01/07/2010

Code: Amber

IDENTIFICATION

Product Name: **DRIBOND CRYSTAL PLUG**

UN Number: None Allocated

Dangerous Goods Class: None Allocated

Subsidiary Risk Class: Not Listed

Hazchem Code: None Allocated

Packaging Group: None Allocated

Poisons Schedule: None Allocated

Use: A cement based waterproofing compound for cement based substrates.

Not classified as hazardous according to criteria of Worksafe Australia.

Physical Description/Properties

Appearance: A light coloured finely divided cement type powder

Boiling Point (°C) : Not Applicable

Vapour Pressure(kPa): Not Applicable

Specific Gravity: 3

Flash Point(°C): Not applicable

Flammability Limits: Not applicable

Solubility in Water: Only slight

Ingredients

Proprietary blend of Cement, Sand, Inorganic fillers and ingredients determined not hazardous.

Caution: contains cement which contains silica

HEALTH HAZARD INFORMATION

Health Effects

Swallowed - Classified as an inert nuisance dust. Exposure can irritate skin, eyes and mucous membrane.

Eye - In dust form may cause inflammation of the cornea.

Skin - Irritant when wet which can dry the skin and cause alkali burns. Slight possibility of causing dermatitis.

Inhaled - As a dust can irritate mucous membrane.

First Aid

Swallowed - Wash mouth and lips with water and seek medical attention

Eye - Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.

Skin - Wash off with tepid soap and water. Remove contaminated clothing and launder before re-use.

Inhalation - Move to fresh air, wash with water and seek medical attention if effects persist.

PRECAUTIONS FOR USE

Exposure Limits - Classified as an inert nuisance dust.

Ventilation - Where practical, suitable means of dust extraction should be applied as necessary to maintain acceptable levels. Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

Personal Protection - In dusty environments, the use of filter masks complying with AS1716 (class L) and tight fitting goggles is advised. Use of barrier creams or impervious gloves, boots and clothing to protect skin from contact with dust and wet product is recommended.

Flammability - Dribond Crystal Plug is not combustible.

SAFE HANDLING INFORMATION

Storage and Transport - Product should be stored in a dry place and protected from ingress of moisture, as this will cause it to harden in storage.

Spills and Disposal - Spills may be cleaned up by any dry method such as broom, shovel or vacuum device. Take care to minimise dust. Clean up personnel should wear full cover clothing, gloves, boots, dust masks and goggles.

Fire/Explosion Hazard - Dribond Crystal Plug poses no hazard.

All information in this data sheet is as accurate and up-to-date as possible. Since Construction Chemicals cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Construction Chemicals will not be responsible for damages of any nature resulting from use of or reliance upon the information.