

# Material Safety Data Sheet

**PRODUCT NAME DRIBOND FOAMGRIP**

## 1. IDENTIFICATION OF THE MATERIAL AND SUPPLIER

**Supplier Name** CONSTRUCTION CHEMICALS  
**Address** 135 Cormack Road, Wingfield, SA, AUSTRALIA, 5013  
**Telephone** SA (08) 8243 7888, QLD (07) 3271 2944, VIC (03) 9761 4711  
**Fax** SA (08) 8243 7800; QLD (07) 3271 3892; VIC (03) 9761 4748  
**Emergency** SA (08) 8243 7888, QLD (07) 3271 2944, VIC (03) 9761 4711  
**Email** conchem.qld@bigpond.com.au  
**Web Site** <http://www.constructionchemicals.com.au/>

**Synonym(s)** FOAMGRIP • CONSTRUCTION CHEMICALS DRIBOND FOAMGRIP

**Use(s)** ADHESIVE

**MSDS Date** 03 April 2008

## 2. HAZARDS IDENTIFICATION

**CLASSIFIED AS HAZARDOUS ACCORDING TO NOHSC CRITERIA****RISK PHRASES**

R36/37/38 Irritating to eyes, respiratory system and skin.  
R42/43 May cause sensitisation by inhalation and skin contact.

**SAFETY PHRASES**

S1/2 Keep locked up and out of reach of children.  
S26 In case of contact with eyes, rinse immediately with plenty of water and seek medical advice.  
S28 After contact with skin, wash immediately with plenty of water.  
S36/37 Wear suitable protective clothing and gloves.  
S38 In case of insufficient ventilation, wear suitable respiratory equipment.  
S45 In case of accident or if you feel unwell seek medical advice immediately (show the label where possible).

**NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

<b>UN No.</b>	None Allocated	<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Pkg Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>EPG</b>	None Allocated

## 3. COMPOSITION / INFORMATION ON INGREDIENTS

Ingredient	Formula	CAS No.	Content
DIPHENYLMETHANE DIISOCYANATE (MDI)	C15-H10-N2-O2	101-68-8	<10%
LIGHT PETROLEUM DISTILLATES, HYDROTREATED	Not Available	64742-47-8	<10%
POLYMETHYL POLYPHENYL ISOCYANATE	Not Available	9016-87-9	<10%
FILLERS	Not Available	Not Available	30-60%
MDI PREPOLYMER	Not Available	53862-89-8	10-30%

# AMBER

PRODUCT NAME **DRIBOND FOAMGRIP**

## 4. FIRST AID MEASURES

<b>Eye</b>	If in eyes, hold eyelids apart and flush the eye continuously with running water. Continue flushing until advised to stop by the PIC or a doctor, or for at least 15 minutes.
<b>Inhalation</b>	If inhaled, remove from contaminated area. To protect rescuer, use a Type A (Organic vapour) respirator or Air-line respirator (in poorly ventilated areas). Apply artificial respiration if not breathing.
<b>Skin</b>	If skin or hair contact occurs, remove contaminated clothing and flush skin and hair with running water. Continue flushing with water until advised to stop by the PIC or a doctor.
<b>Ingestion</b>	For advice, contact a Poison Information Centre on 13 11 26 (Australia Wide) or a doctor (at once). If swallowed, do not induce vomiting.
<b>Advice to Doctor</b>	Treat symptomatically.
<b>First Aid Facilities</b>	Eye wash facilities and safety shower are recommended.

## 5. FIRE FIGHTING MEASURES

<b>Flammability</b>	Combustible. May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons, hydrogen cyanide, isocyanates) when heated to decomposition.
<b>Fire and Explosion</b>	Combustible. Evacuate area and contact emergency services. Toxic gases (hydrocarbons, carbon/ nitrogen oxides, isocyanates, hydrogen cyanide) may be evolved. Remain upwind and notify those down wind of hazard. Wear full protective equipment including Self Contained Breathing Apparatus (SCBA) when combating fire. Use waterfog to cool intact containers and nearby storage areas.
<b>Extinguishing</b>	Dry agent, carbon dioxide or water fog. Prevent contamination of drains or waterways.
<b>Hazchem Code</b>	None Allocated

## 6. ACCIDENTAL RELEASE MEASURES

<b>Spillage</b>	If spilt (bulk), contact emergency services. Wear splash-proof goggles, viton gloves, a Type A (Organic vapour) respirator or Full-face Air-line respirator, coveralls & boots. Ventilate. Clear area of all unprotected personnel. Add decontaminant solution (90% water, 8% ammonia, 2% detergent) and allow 10 minutes for reaction, alternatively add water and allow 30 minutes for reaction. Absorb with sand or similar and place in a container.
-----------------	--

## 7. STORAGE AND HANDLING

<b>Storage</b>	Store in cool, dry, well ventilated area, removed from oxidising agents, acids, alkalis, alcohol, amines, direct sunlight, moisture, heat or ignition sources & food stuffs. Ensure containers are adequately labelled, protected from physical damage & sealed when not in use. Check regularly for leaks or spills. Large storage areas should have appropriate fire protection and ventilation. Store as a Class C1 Combustible Liquid (AS1940).
<b>Handling</b>	Before use carefully read the product label. Use of safe work practices are recommended to avoid eye or skin contact and inhalation. Observe good personal hygiene, including washing hands before eating. Prohibit eating, drinking and smoking in contaminated areas.

## 8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Exposure Stds	Ingredient	Reference	TWA		STEL	
			ppm	mg/m3	ppm	mg/m3
	Isocyanates, all (as-NCO)	NOHSC (AUS)	0.02	0.07	--	--
	Isocyanates, all (as-NCO)	NOHSC (AUS)	0.02	0.07	--	--

**Biological Limits** No biological limit allocated.


# AMBER

## PRODUCT NAME DRIBOND FOAMGRIP

**Engineering Controls** Do not inhale vapours. Use in well ventilated areas. In poorly ventilated areas, mechanical extraction ventilation is recommended.

**PPE** Wear splash-proof goggles, nitrile or viton (R) gloves and coveralls.

If spraying, with prolonged use, or if in confined areas, wear an Air-line respirator.



## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Appearance</b>	VISCOUS BROWN LIQUID	<b>Solubility (water)</b>	INSOLUBLE
<b>Odour</b>	SLIGHT ODOUR	<b>Specific Gravity</b>	NOT AVAILABLE
<b>pH</b>	NOT AVAILABLE	<b>% Volatiles</b>	NOT AVAILABLE
<b>Vapour Pressure</b>	NOT AVAILABLE	<b>Flammability</b>	CLASS C1 COMBUSTIBLE
<b>Vapour Density</b>	NOT AVAILABLE	<b>Flash Point</b>	73°C
<b>Boiling Point</b>	NOT AVAILABLE	<b>Upper Explosion Limit</b>	NOT AVAILABLE
<b>Melting Point</b>	NOT AVAILABLE	<b>Lower Explosion Limit</b>	NOT AVAILABLE
<b>Evaporation Rate</b>	NOT AVAILABLE	<b>Autoignition Temperature</b>	NOT AVAILABLE

## 10. STABILITY AND REACTIVITY

**Chemical Stability** Stable under recommended conditions of storage.

**Conditions to Avoid** Avoid heat, sparks, open flames and other ignition sources.

**Material to Avoid** Incompatible with oxidising agents, acids, alcohols, amines, alkalis, heat and ignition sources. Reacts with water or moisture, generating carbon dioxide, which may cause container rupture.

**Decomposition** May evolve toxic gases (carbon/ nitrogen oxides, hydrocarbons, hydrogen cyanide, isocyanates) when heated to decomposition.

**Hazardous Reactions** Polymerization is not expected to occur.

## 11. TOXICOLOGICAL INFORMATION

**Health Hazard Summary** Toxic. Use safe work practices to avoid eye-skin contact and vapour inhalation. When mixed with isocyanate component, over exposure to free isocyanate monomers may result in skin and respiratory sensitisation. Chronic or high level exposure to isocyanates may result in permanent lung damage. Those individuals previously sensitised to isocyanates are advised to avoid ALL exposure.

**Eye** Irritant. Contact may result in irritation, lacrimation, pain, redness, conjunctivitis. May result in burns with prolonged contact.

**Inhalation** Irritant. Over exposure may result in irritation of the nose and throat, nausea, vomiting and sensitisation with asthma-like symptoms. At high levels; dizziness, breathing difficulties and pulmonary oedema. Chronic exposure may result in permanent lung impairment.

**Skin** Irritant. Contact may result in irritation, redness, rash and dermatitis. Potential sensitising agent. May be absorbed through skin with toxic effects.

**Ingestion** Toxic. Ingestion may result in nausea, vomiting, abdominal pain, diarrhoea, fatigue, dizziness and unconsciousness. Aspiration may result in chemical pneumonitis and pulmonary oedema.

**Toxicity Data**  
DIPHENYLMETHANE DIISOCYANATE (MDI) (101-68-8)  
LC50 (Inhalation): 178 mg/m<sup>3</sup> (rat)  
LD50 (Ingestion): 2200 mg/kg (mouse)  
POLYMETHYL POLYPHENYL ISOCYANATE (9016-87-9)  
LC50 (Inhalation): 490 mg/m<sup>3</sup>/4 hours (rat)  
LD50 (Ingestion): 49,000 mg/kg (rat)

# AMBER

PRODUCT NAME **DRIBOND FOAMGRIP**

LD50 (Skin): > 9400 mg/kg (rabbit)

## 12. ECOLOGICAL INFORMATION

**Environment** Isocyanates will react with water producing carbon dioxide and forming a solid mass (polyurea) which is insoluble. Product will not accumulate or biomagnify in the environment.

## 13. DISPOSAL CONSIDERATIONS

**Waste Disposal** For small amounts absorb with sand, vermiculite or similar and dispose of to an approved landfill site. Contact the manufacturer for additional information if larger amounts are involved. Prevent contamination of drains and waterways as aquatic life may be threatened and environmental damage may result.

**Legislation** Dispose of in accordance with relevant local legislation.

## 14. TRANSPORT INFORMATION

**NOT CLASSIFIED AS A DANGEROUS GOOD BY THE CRITERIA OF THE ADG CODE**

<b>Shipping Name</b>	None Allocated				
<b>UN No.</b>	None Allocated	<b>DG Class</b>	None Allocated	<b>Subsidiary Risk(s)</b>	None Allocated
<b>Pkg Group</b>	None Allocated	<b>Hazchem Code</b>	None Allocated	<b>EPG</b>	None Allocated

## 15. REGULATORY INFORMATION

**Poison Schedule** A poison schedule number has not been allocated to this product using the criteria in the Standard for the Uniform Scheduling of Drugs and Poisons (SUSDP).

**AICS** All chemicals listed on the Australian Inventory of Chemical Substances (AICS).

## 16. OTHER INFORMATION

**Additional Information** ISOCYANATES: Asthma sufferers, respiratory impaired or previously sensitised individuals are advised to avoid all exposure to isocyanates. Please note that products containing isocyanates often require the preparation of safe working procedures before product is used.

EPOXY - PHENOXY RESINS AND POLYURETHANES: Where spray painting with two or more component epoxy resins or polyurethane paints is undertaken, an employee shall wear a air-line respirator, full length chemically resistant coveralls and gloves. Further, if an individual is to enter an enclosed booth where a vapour or gas curing process is occurring, an air-line respirator is required. Once cured, these resins are considered non toxic.

### ABBREVIATIONS:

ADB - Air-Dry Basis.

BEI - Biological Exposure Indice(s)

CAS# - Chemical Abstract Service number - used to uniquely identify chemical compounds.

CNS - Central Nervous System.

EINECS - European INventory of Existing Commercial chemical Substances.

IARC - International Agency for Research on Cancer.

M - moles per litre, a unit of concentration.

mg/m<sup>3</sup> - Milligrams per cubic metre.

NOS - Not Otherwise Specified.

NTP - National Toxicology Program.

OSHA - Occupational Safety and Health Administration.

pH - relates to hydrogen ion concentration using a scale of 0 (high acidic) to 14 (highly alkaline).

ppm - Parts Per Million.

RTECS - Registry of Toxic Effects of Chemical Substances.

TWA/ES - Time Weighted Average or Exposure Standard.

### HEALTH EFFECTS FROM EXPOSURE:

It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a Chem Alert report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

### PERSONAL PROTECTIVE EQUIPMENT GUIDELINES:

**AMBER**

**PRODUCT NAME DRIBOND FOAMGRIP**

The recommendation for protective equipment contained within this Chem Alert report is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

COLOUR RATING SYSTEM: RMT has assigned all Chem Alert reports a colour rating of Green, Amber or Red for the sole purpose of providing users with a quick and easy means of determining the hazardous nature of a product. Safe handling recommendations are provided in all Chem Alert reports so as to clearly identify how users can control the hazards and thereby reduce the risk (or likelihood) of adverse effects. As a general guideline, a Green colour rating indicates a low hazard, an Amber colour rating indicates a moderate hazard and a Red colour rating indicates a high hazard.

While all due care has been taken by RMT in the preparation of the Colour Rating System, it is intended as a guide only and RMT does not provide any warranty in relation to the accuracy of the Colour Rating System. As far as is lawfully possible, RMT accepts no liability or responsibility whatsoever for the actions or omissions of any person in reliance on the Colour Rating System.

**Report Status**

This document has been compiled by RMT on behalf of the manufacturer of the product and serves as the manufacturer's Material Safety Data Sheet ('MSDS').

It is based on information concerning the product which has been provided to RMT by the manufacturer or obtained from third party sources and is believed to represent the current state of knowledge as to the appropriate safety and handling precautions for the product at the time of issue. Further clarification regarding any aspect of the product should be obtained directly from the manufacturer.

While RMT has taken all due care to include accurate and up-to-date information in this MSDS, it does not provide any warranty as to accuracy or completeness. As far as lawfully possible, RMT accepts no liability for any loss, injury or damage (including consequential loss) which may be suffered or incurred by any person as a consequence of their reliance on the information contained in this MSDS.

**Prepared By**

Risk Management Technologies  
5 Ventnor Ave, West Perth  
Western Australia 6005  
Phone: +61 8 9322 1711  
Fax: +61 8 9322 1794  
Email: info@rmt.com.au  
Web: www.rmt.com.au

**MSDS Date:** 03 April 2008

**End of Report**