

# CONSTRUCTION CHEMICALS

## CERAMIC TILE ADHESIVES & GROUTS

# Dribond

WATERPROOFING PRODUCTS  
FOR CONCRETE AND MASONRY

### WEB SITE

[www.constructionchemicals.com.au](http://www.constructionchemicals.com.au)

**Adelaide**  
135 Cormack Rd  
Wingfield S.A. 5013  
Ph: (08) 82437888  
Fax: (08) 82437800  
Email  
[admin@constructionchemicals.com.au](mailto:admin@constructionchemicals.com.au)  
ABN 66 008 091 503

**Brisbane**  
45 Coulson Street  
Wacol, Qld 4076  
Ph (07) 32712944  
Fax (07) 32713892  
Email  
[conchem.qld@bigpond.com.au](mailto:conchem.qld@bigpond.com.au)

**Melbourne**  
11 Gabrielle Court  
Bayswater North Vic 3153  
Ph (03) 97614711  
Fax (03) 97614748

**Perth**  
11 Collie Road  
Welshpool W.A. 6106  
Ph (08) 93569999  
Fax (08) 93569955

**Sydney**  
2 / 31-33 Newton Road  
Wetherill Park N.S.W. 2164  
Ph (02) 97563533  
Fax (02) 97563534

**Auckland**  
16 Carpenter Road  
East Tamaki N.Z.  
Ph (09) 2735444  
Fax 0800266236

**Kuala Lumpur**  
Lot 2 Jalan Kecepi,  
33/2 Elite Industrial Estate  
Off Jalan Bukit Kemuning  
40000 Shah Alam  
Ph (603) 51222522  
Fax (603) 51222526

## MATERIAL SAFETY DATA SHEET

Issued 9/10/2000  
Revised 01/07/2010  
Code Amber

### IDENTIFICATION

Product Name: **KEMGROUT FLEXIBLE**  
UN Number: None Allocated  
Dangerous Goods Class: None Allocated  
Subsidiary Risk Class: Not Listed  
Hazchem Code: None Allocated  
Packaging Group: None Allocated  
Poisons Schedule: None Allocated  
Use: Cement based tile grout

**Not classified as hazardous according to criteria of Worksafe Australia.**

### Physical Description/Properties

Appearance: A coloured finely divided cement type powder  
Boiling Point (°C): Not Applicable  
Vapour Pressure(kPa): Not Applicable  
Specific Gravity: 3  
Flash Point(°C): Not applicable  
Flammability Limits: Not applicable  
Solubility in Water: Only slight

### Ingredients

Proprietary blend of Cement, Inorganic fillers, Inorganic Oxide Pigments and ingredients determined not hazardous

Caution: contains cement which contains silica

### HEALTH HAZARD INFORMATION

#### Health Effects

**Swallowed** - Classified as an inert nuisance dust. Exposure can irritate skin, eyes and mucous membrane.

**Eye** - In dust form may cause inflammation of the cornea.

**Skin** - Irritant when wet which can dry the skin and cause alkali burns. Slight possibility of causing dermatitis.

**Inhaled** - As a dust can irritate mucous membrane.

#### Health Effects - Chronic

May cause sensitization in susceptible individuals by skin contact. Allergic response and as dermatitis or asthma like symptoms may occur after a single significant exposure and sensitization may occur on a single or multiple minor exposures.

If cured material made using this product is to be cut or sanded, ensure an appropriate dusk mask (class P1, disposable) is worn. In addition industrial safety glasses or goggles should also be worn.

**First Aid**

**Swallowed** - Wash mouth and lips with water and seek medical attention

**Eye** - Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.

**Skin** - Wash off with tepid soap and water. Remove contaminated clothing and launder before re-use.

**Inhalation** - Move to fresh air, wash with water and seek medical attention if effects persist.

**PRECAUTIONS FOR USE**

**Exposure Limits** - Classified as an inert nuisance dust.

**Ventilation** - Where practical, suitable means of dust extraction should be applied as necessary to maintain acceptable levels. Persons with a history of respiratory illness or reduced pulmonary function should avoid work places with high dust levels.

**Personal Protection** - In dusty environments, the use of filter masks complying with AS1716 ( class L ) and tight fitting goggles is advised. Use of barrier creams or impervious gloves, boots and clothing to protect skin from contact with dust and wet product is recommended.

**Flammability** – Kemgrout Flexible is not combustible.

**SAFE HANDLING INFORMATION**

**Storage and Transport** - Product should be stored in a dry place and protected from ingress of moisture, as this will cause it to harden in storage.

**Spills and Disposal** - Spills may be cleaned up by any dry method such as broom, shovel or vacuum device. Take care to minimise dust. Clean up personnel should wear full cover clothing, gloves, boots, dust masks and goggles.

**Fire/Explosion Hazard** – Kemgrout Flexible poses no hazard.

All information in this data sheet is as accurate and up-to-date as possible. Since Construction Chemicals cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Construction Chemicals will not be responsible for damages of any nature resulting from use of or reliance upon the information.