

**CERAMIC TILE
ADHESIVES
& GROUTS**

Dribond

**WATERPROOFING PRODUCTS
FOR CONCRETE AND MASONRY**

WEB SITE

www.constructionchemicals.com.au

Adelaide

135 Cormack Rd
Wingfield S.A. 5013
Ph: (08) 82437888
Fax: (08) 82437800
Email

admin@constructionchemicals.com.au

ABN 66 008 091 503

Brisbane

45 Coulson Street
Wacol, Qld 4076
Ph (07) 32712944
Fax (07) 32713892
Email

conchem.qld@bigpond.com.au

Melbourne

11 Gabrielle Court
Bayswater North Vic 3153
Ph (03) 97614711
Fax (03) 97614748

Perth

11 Collie Road
Welshpool W.A. 6106
Ph (08) 93569999
Fax (08) 93569955

Sydney

2 / 31-33 Newton Road
Wetherill Park N.S.W. 2164
Ph (02) 97563533
Fax (02) 97563534

Auckland

16 Carpenter Road
East Tamaki N.Z.
Ph (09) 2735444
Fax 0800266236

Kuala Lumpur

Lot 2 Jalan Kecepi,
33/2 Elite Industrial Estate
Off Jalan Bukit Kemuning
40000 Shah Alam
Ph (603) 51222522
Fax (603) 51222526

MATERIAL SAFETY DATA SHEET

Issued 22/3/2001
Revised 01/07/2010
Code Green

IDENTIFICATION

Product Name: **ROLTEX**
UN Number: None Allocated
Dangerous Goods Class: None Allocated
Subsidiary Risk Class: Not Listed
Hazchem Code: None Allocated
Packaging Group: None Allocated
Poisons Schedule: None Allocated
Use: A flexible acrylic coating for concrete and masonry.

Not classified as hazardous according to criteria of Worksafe Australia.

Physical Description/Properties

Appearance: White liquid, high viscosity
Boiling Point (°C) : None Allocated
Vapour Pressure(kPa): None Allocated
Specific Gravity: 1.4 @ 15°C
Flash Point(°C): Not Applicable
Flammability Limits: None
Solubility in Water: Miscible

Ingredients

Acrylic Polymer, inert fillers and ingredients determined not hazardous

HEALTH HAZARD INFORMATION

Health Effects

Swallowed - May cause irritation to mouth, throat and digestive tract. Large dose may cause drowsiness and may lead to unconsciousness.

Eye - May be irritating to the eyes.

Skin - Irritant. Avoid prolonged or repeated contact as may cause dermatitis.

Inhaled - Vapour is irritant to mucous membranes and respiratory tract. Vapours can affect the central nervous system and result in headaches and dizziness. High concentrations of vapour, if exposure is prolonged, may cause unconsciousness. Aspiration of liquid into lungs can cause serious (even fatal) pneumonitis.

First Aid

Swallowed - If poisoning occurs, contact a doctor or Poisons information centre. If swallowed, do not induce vomiting. Give glass of water. If any suspicion of aspiration into lungs obtain medical advice immediately.

Eye - Irrigate with copious quantities of water. If soreness or redness persists, seek medical attention.

Skin - Wash off with soap and water. Remove contaminated clothing and launder before re-use.

Inhalation - Move to fresh air, keep warm and at rest. Seek medical attention. Apply artificial respiration if not breathing.

Advice to Doctors

Because of risk of aspiration, gastric lavage should only be undertaken after endotracheal intubation.

PRECAUTIONS FOR USE

Exposure Limits - 100 ppm 8 hour time weighted average.

Ventilation - Avoid breathing vapour. Use in well ventilated area. Local exhaust ventilation usually required. Ensure ventilation is adequate to maintain air concentrations below exposure standards.

Personal Protection - Avoid eye and skin contact. Wear chemical goggles or faceshield. Wear breathing apparatus in confined areas.

Flammability - Avoid heat and sources of ignition. Prevent build-up of flammable vapours.

SAFE HANDLING INFORMATION

Storage and Transport - Avoid contact with strong oxidising agents. Store in cool well ventilated area away from heat and ignition sources. Containers should always be kept in storage properly labelled. Store only in original containers.

Spills and Disposal - Keep public away. Extinguish all ignition sources. For major spills, dam and recover. Prevent entry into drainage systems, rivers etc. Collect with absorbent material such as sand, earth or sawdust. Warn occupants downwind. Advise authorities. Ensure waste disposal conforms with local waste disposal regulations. After recovery and evaporation remaining soil may be disposed of to approved landfill, or if approved, allowed to degrade insitu.

Fire/Explosion Hazard - Flammable liquid. Combustion products include oxides of carbon. Use foam, CO₂, dry powder fire extinguishers. Use water sprays to cool fire exposed surfaces and any adjacent storage vessels. Shut off source of product if it is safe to do so. Remove sources of re-ignition. Vapour/Air mixture may ignite explosively. Flashback along vapour trail may occur.

All information in this data sheet is as accurate and up-to-date as possible. Since Construction Chemicals cannot anticipate or control the conditions under which this information may be used, each user should review the information in the specific context of the intended application. Construction Chemicals will not be responsible for damages of any nature resulting from use of or reliance upon the information.