

Dribond Concrete Hardener

CHEMICALLY HARDENS CONCRETE FLOORS

PACKAGING



MIXING



APPLICATION



USES



SUBSTRATES



DESCRIPTION

A clear fluosilicate solution that case hardens poorly-cured cement masonry structures by impregnating into its capillary spaces and then by chemically reacting with the free lime it bonds and strengthens the crystalline structure.

USES

Apply to concrete and terrazzo floors, concrete block and cement render walls in factories, warehouses, food processing plants, bakeries, dairies and piggeries to improve their durability and life. Applied to limestone or soft high lime content walls it will help prevent sweating.

FEATURES

- Easy to apply – sweep or brush on with a broom, mop or squeegee
- Permanently case hardens dusty or soft concrete or cement base structures by up to 300% of untreated concrete
- Dustproofs by bonding and strengthening the cement's crystalline structure
- Substantially increases the chemical and abrasion resistance
- Seals the structure against moisture penetration.

COVERAGE (Approximate)

Allow at least 1 litre per 4 m² per coat (two coats are required).

PERFORMANCE DATA

Improves the abrasion resistance of dusty or poorly cured concrete by up to 3 times. Has good resistance to alkali solution and petroleum solvents but poor resistance to strong acids.

SPECIFICATION

The floor hardener shall chemically case harden the concrete surface such as CONCRETE HARDENER manufactured by Construction Chemicals and shall be applied in accordance with the manufacturers instructions.

APPLICATION

New Surfaces must have cured for at least 14 days and be free from curing compounds, dirt, dust and other contaminants.

Existing Surfaces must be free of dirt, dust, wax, grease and other contaminants.

Remove contaminants by washing the floor thoroughly and allow to dry completely.

Apply two coats of CONCRETE HARDENER at the rate of 1 litre per 4 m² per coat, allowing the first coat to dry for 4-6 hours before applying the second. Apply with a mop, hair broom or squeegee. Clean down equipment with water.

PRECAUTIONS

- Avoid contact with eyes, open wounds etc.
Wash affected area thoroughly with water.
- Apply only under good ventilation.
- The solution is highly corrosive.
- Do not store for long periods.

SHELF LIFE

2 years

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** 135 CORMACK RD (Cnr Davis St) WINGFIELD 5013 PH: (08) 8243 7888 FAX: (08) 8243 7800
 ● **BRISBANE** 45 COULSON ST WACOL 4076 PH: (07) 3271 2944 FAX: (07) 3271 3892
 ● **MELBOURNE** 11 GABRIELLE CT BAYSWATER NORTH 3153 PH: (03) 9761 4711 FAX: (03) 9761 4748
 ● **PERTH** 11 COLLIE ST WELSHPOOL 6106 PH: (08) 9356 9999 FAX: (08) 9356 9955
 ● **SYDNEY** 31-33 NEWTON RD WETHERILL PARK 2164 PH: (02) 9756 3533 FAX: (02) 9756 3534
 ● **AUCKLAND** 16 CARPENTER RD EAST TAMAKI PH: (09) 273 5444 FAX: 0800 266 236
 ● **KUALA LUMPUR** LOT 2 JALAN KECAPI 33/2 ELITE INDUSTRIAL ESTATE OFF JALAN BUKIT KEMUNING
 40000 SHAB ALAM PH: (603) 5122 2522 FAX: (603) 5122 2526

www.constructionchemicals.com.au

"The information contained in this technical publication is based on our current knowledge and experience and is provided as a guide only. In view of the many factors that may affect application it is the users sole responsibility to ensure suitability for a specific purpose."

Modified June 2008