

2 COMPONENT LIQUID AND POWDER WATER-RESISTANT BONDING PRIMER

PACKAGING



MIXING



APPLICATION



DESCRIPTION

PRIMAX is a two pack, water resistant bonding primer with exceptional adhesion to difficult to adhere to surfaces.

USES

PRIMAX will adhere to porous and non-porous surfaces that are difficult to adhere to, if they are clean, structurally sound and uncontaminated i.e.

- Helicoptered (smooth finish) concrete
- Immersed applications
- Glazed ceramic tiles
- External areas.
- Compressed cement sheet.

FEATURES

- **Eliminates the need to mechanically roughen or acid etch concrete**
- **Water resistant**
- **Ideal as a primer over ceramic tiles.**

COVERAGE

5L/5kg covers 20m².

SURFACE PREPARATION

The substrate must be structurally sound, clean and free from dust, dirt, waxes, release agents, curing compounds and all other contaminants. Ceramic tiles, stone must be cleaned to remove waxes and grease with an industrial grade detergent then thoroughly washed clean.

CAUTION: If the surface is contaminated (eg. sealer, coating or porcelain tiles) mechanically abrade. **If in doubt a test area must be done.**

MIXING

Place 1 litre of liquid in a mixing container and mix in 1kg of powder mixing to uniform creamy consistency. Always add powder to the liquid. Allow to stand for 5-10 minutes and restir before use.

APPLICATION

Apply the mixed PRIMAX only with a hard brush or broom, making sure to push the mixture firmly into the substrate. Apply mixture approximately 0.5mm thick and allow to cure 1-2 hours at 23°C @ 50% relative humidity before proceeding.

CLEAN UP

Uncured material can be cleaned up in water.

SUBSTRATES

CONCRETE FLOORS
CERAMIC TILES

**CONSTRUCTION
CHEMICALS**

● **ADELAIDE** PH: (08) 8243 7888

● **BRISBANE** PH: (07) 3271 2944

● **DARWIN** PH: (08) 89471811

● **MELBOURNE** PH: (03) 9761 4711

● **PERTH** PH: (08) 9356 9999

● **SYDNEY** PH: (02) 9756 3533

● **AUCKLAND** PH: (09) 273 5444

● **KUALA LUMPUR** PH: (603) 5122 2522

www.constructionchemicals.com.au